


NOTES

1. FOR PEDESTRIAN CORRIDOR SIGN LAYOUT AND PAVEMENT MARKING LAYOUT SEE POLICY # 100-C-2.
2. UNDERGROUND ELECTRICAL CONDUIT TRENCHED FROM BASE TO BASE AND FROM ONE BASE TO ELECTRICAL SERVICE POLE.
3. BEACONS TO FLASH ALTERNATELY.
4. MOUNTING HEIGHT FOR ALL RA-4 SIGNS 2.5 METERS (BOTTOM OF SIGN) ABOVE SIDEWALK.
5. MOUNTING HEIGHT FOR ALL PUSH BUTTONS 1.0 METERS ABOVE SIDEWALK.
6. WALKING PEDESTRIAN SYMBOL SHALL ALWAYS BE DIRECTED AWAY FROM CURB.
7. LOCATION: NON-DIVIDED HIGHWAY.
8. E-049D AND E-049E SEE WRITTEN PEDESTRIAN CORRIDOR HEAD SPECIFICATIONS.

REVISIONS	DATE	DESCRIPTION	BY
05-09		PAPER ORIGINAL	MEM

Manitoba 
 Infrastructure and
 Transportation
 TRAFFIC ENGINEERING

TYPICAL PEDESTRIAN CORRIDOR

ORIGINAL APPROVED BY: _____ LUCIEN GAGNON _____

SCALE:	N.T.S.
DATE:	06-2005
PREP. BY:	H.A.E
E-019a	