


NOTES:

- REINFORCING PLATE GOES ON TOP WHEN HEAD IS HANGING, BUT ON BOTTOM WHEN HEAD MOUNTED ON ARMS. (NOT REQUIRED ON POLYCARBONET HEAD)
- IN A 3-SECTION SIGNAL HEAD THE LEFT TURN ARROW LED LENS IS NOT A BIMODAL.
- ALL LENSES ARE LED.
- SUPPORT STRAPPING SHALL BE STEEL HEAVY DUTY "SIGNODE" TYPE Z.R. COATED/GALVANIZED 19 mm WIDE/0.61 mm THICK USING "SIGNODE", #703 COATED/GALVANIZED SEALS. (SUBSTITUTES MAY BE APPROVED BY THE ENGINEER)
- RISER CABLE EXISTING POLE MUST HAVE A DRIP LOOP.
- INSULATED BUSHING REQUIRED WHERE RISER CABLE ENTERS POLE.

REVISIONS	DATE	DESCRIPTION	BY

Manitoba 
 Infrastructure and
 Transportation
 TRAFFIC ENGINEERING

LIGHT SERIES 2.5 METER DAVI
 Type 2
 ORIGINAL
 APPROVED BY: LUCIEN GAGNON

SCALE:	N.T.S.
DATE:	MAY/06
PREP. BY:	H.A.E.
E-112c	